

## PD - 50

Paket Yay Çiftli Dizgi Makinası

Pocket Spring Twin Assembly Machine

### TECHNICAL SPECIFICATION

Spring type: Barrell or cylindrical  
Spring Diameter: 50-70 mm  
Spring Height: 100-190 cm  
Max width: 2000 mm  
Cycle time: 10 sec. /row  
Gluing type: Continuous or bead  
Controls: PLC Control, frequency inverters and control panel  
Spring Unit: Parallel or Nested or Zoning  
Fabric Rolls: Pad Max. 900 mm - Weight Max. 70 Kg  
Holt Melt Glue Tank: Robatech Concept 30 Lit.  
Power Requeriments: 380 V 3 phases 50 hertz 11KW  
Air Consumption: 6 Bar  
Weight: Approx. 1950 Kg including hotmelt unit 30 Litre

\*\*\*Note: Please consult with us about special sizes

### TEKNİK ÖZELLİKLER

Yay Tipi: fıçı veya silindirik  
Yay kafa çapı: 50-70 mm  
Yay yüksekliği: 100-190 mm  
Maksimum en: 2000 mm  
Çalışma hızı : 10 saniye / sıra  
Tutkal atım tipi: sürekli veya kesik  
Kontrol: PLC kontrollü, frekans kontrolü ve kontrol paneli  
Çalışma sistemi: Paralel veya zigzag veya bölgesel  
Holt Melt Yapıştırıcı tankı: Robatech Concept 30 Litre.  
Şebeke: 380 V 3 faz 50 hertz 11KW  
Hava basıncı: 6 Bar  
Ağırlık:Yapıştırıcı tankı dahil yaklaşık 1950 Kg

